

LED CANOPY LIGHT / LOWBAY

Primo 15K Canopy Light

100W 15,000 lm

DIMMABLE 1-10VDC



Canopy light for low ceilings & clean rooms
 Outstanding 150 lumens/watt performance
 Dimmable to 10% output with motion sensors
 Simple flush-mounted installation.

primo-
 FIRST FOR HIGH PERFORMANCE LED CANOPY LIGHTING



-150 LUMENS PER WATT



50,000+ HOURS



IP65 RATING



115° BEAM



RA >80 CRI
 5000K



PLUG & PLAY LIGHT / MOTION SENSORS



5 YEAR WARRANTY

HIGH PERFORMANCE CANOPY LIGHT FOR 4-8M+ CEILINGS

15,000 lumens from 100W at 150 lm/W
 Outstanding efficiency - latest high performance LEDs
 Dimmable driver for use with optional lighting controls
 Wide 115 degree beam spread for even light distribution
 Bright white 5,000K light. Low glare design
 Rated IP65 and for operating temps from -30 to +50°C
 Food-safe design with heavy duty PMMA acrylic lens
 50,000+ hour service life and 5 year warranty.

APPLICATIONS


- Flush-mounted lowbays for lower ceilings.
- Food and pharmaceutical industries, or sites with hot water and detergent washdowns.
- Hot, cold, moist and dusty environments.

DESIGNED AND BUILT IN KOREA FOR EXTRA HEAVY DUTY




DIMMABLE 1-10VDC - COMPATIBLE WITH SENSORS


Compatible with Primo IQ occupancy & light sensors.
 Enables auto-dimming which can be pre-programmed area by area, via remote control.
 Auto-dimming individual lights with light or occupancy sensors eliminates power wastage when light is not needed, cutting lighting costs by up to 90%.



PHYSICAL DIMENSIONS



- Reduced glare design for low ceiling heights
- Wide 115 degree beam spread
- Recessed design



- Complies with Food Safety Standards
- PMMA acrylic lens standard - no glass
- Sleek design for easy cleaning

DESIGNED FOR EASY INSTALLATION

- Connectors on DC cable from driver to fitting allow quick and simple installation from below the ceiling
- Fitting secured from below by 4 screws

Cut-outs: Round - 4 in / 10cm diameter.
 Square - 8-11 in / 20-28 cm.

ILLUMINANCE (115 deg)
 (Lux, Beam Diameter, Height)

5467 lux	3.2m	1m
1367	6.4	2
607	9.6	3
342	12.8	4
219	16.0	5
152	19.2	6
112	22.3	7
85	25.5	8

TECHNICAL PARAMETERS

Power consumption	100W
Input voltage & frequency	100-277VAC; 50/60Hz
Power factor	-0.98
Surge protection	10kV L-FG / 6kV L-L
Driver	Inventronics Dimmable
Dimming	Dimmable 1-10VDC with light & occupancy sensors
LED chips	High performance Samsung, -150 lm/W
Luminous Flux	15,000 lumens
Efficacy	-150lm/W
Colour temperature	5000°K
CRI	RA >80
Light distribution	115 degrees

IP Rating	IP65
Composition - lens plate	Heavy duty PMMA acrylic - no glass
Composition - housing	Cast Aluminium / Aluminium
Working temperature	-30 to +50 °C
Service life	>50,000 hours
Warranty	5 years
Weight	4.0kg
Dimensions	400mm W x 400mm L x 29mm H
Product codes	
Primo 15K Canopy (100W)	HP15K100PM