



- MID- HINGED POLES ARE SPECIFICALLY & INDIVIDUALLY DESIGNED TO BE BALANCED AROUND THE HINGE SO THAT THE POLE CAN BE SWUNG 180° WITH MINIMAL EFFORT BASED ON THE NUMBER AND WEIGHT OF THE FITTINGS ON EACH POLE. MOUNTINGS SHOULD NOT BE ALTERED OTHERWISE THE POLE MAYBE DANGEROUS TO OPERATE. REFER TO GM POLES MID-HINGED POLES OPERATION MANUAL PRIOR TO OPERATION.
- FITTINGS SHOULD NOT BE PLACED ON THE SAME SIDE AS HINGE PIN TO AVOID INTERFERENCE WITH POLE WHEN SWUNG.

|     |            |      |                               |                      |              |            |        |   |            |      |        |
|-----|------------|------|-------------------------------|----------------------|--------------|------------|--------|---|------------|------|--------|
|     |            |      |                               |                      |              |            |        | 490 Freeman Rd.<br>RICHLANDS,<br>QLD 4077<br>Ph: (07) 3718 4900 |            |      |        |
|     |            |      |                               | TIGERLIGHT CORSO PRO |              |            |        |   |            |      |        |
|     |            |      |                               | 6m MID-HINGED POLES  |              |            |        |   |            |      |        |
| 1   | 23/02/2023 | B.D. | POLE MOUNTING HEIGHTS CHANGED | p.d.                 | Drn          | Date       | Scale  | Drawing No  |            |      |        |
| 0   | 22/02/2023 | B.D. | INITIAL ISSUE                 | p.d.                 | B. Donaldson | 22/02/2023 | N.T.S. |   |            |      |        |
| Rev | Date       | Drn  | Description                   | Chk                  | B. Donaldson | 22/02/2023 | N.T.S. |   | CD0010671B | Page | 1 of 1 |