TAILOR-MADE by tigerlight[®]



POWFR & OUTPUT





TEMPERATURE



BRACKETS







iq-LIGHTING **CONTROLS**

Light fittings made exactly to your specifications. And shipped ready to install in 7-8 weeks' time.

> **tige**rlight* **HIGH-PERFORMANCE** INDUSTRIAL LIGHTING

TAILOR-MADE by tigerlight

















Individually designed and constructed to meet your exact requirements.



SPORTS LIGHTING ONLY > **POWER 30W** 80W 120W 200W 320W 480W 720W 960W 1440W 1920W **LUMENS** 4000 11.500 17,000 29,000 45.000 60.000 90.000 125,000 170,000 220,000 lm
















































40W - 400W Spigot 62mm int diam.































COLOURS





- Grey RAL7004 • White RAL9010
- Bronze RAL8019 • RAL colour-match








PC - Stack




COLOUR


TEMPERATURE


























PB - Slim-line








White






GREEN LED 530nm • Emergency eyewash stations




VOLTAGE

OPTIONS



• 240V AC (100-277VAC) • 415V AC (277-480VAC)





- **DALI Dimming**
- PE Cell
- Integrated motion sensor







FLEXIBLE MODULAR PLATFORM OFFERS LIMITLESS OPTIONS

- Fully customisable to suit all applications
- Manufactured and shipped in 7-8 weeks.

From 20W to 1920W. From 3,000 to 221,000 lumens 7 different bracket choices for spigot, wall or ceiling mounts Unlimited housing colour options


Remote driver options

16 Optical lens options, inclu

16 Optical lens options, including symmetrical & asymmetrical CCT options include whites, RGB colours, amber & green 12 or 24VDC. 240 and 415VAC options

Lighting control options

Emergency option (up to 40W fittings).



SOLAR OPTIONS ALSO AVAILABLE

Off-grid solar-powered engine

Large battery capacity to maximise autonomy

Programmable power output to suit the application

For use with Tigerlight luminaires including Mako and Mako Bulkhead, Streetlights, MegaFloods and Sentry area lights.



SOLO 160/130 160W PANEL 130 Ah BATTERY



DELIVERY OF MADE-TO-ORDER ITEMS

Some Tailor-made fittings may be available ex-stock, particularly when the specifications happen to match fittings within the existing Tigerlight range. For fittings which are Tailor-made, please allow up to 6-8 weeks for manufacture and delivery under normal circumstances. Please note that unexpected shipping delays or raw material shortages may impact delivery times. Consult your Tigerlight representative.

TECHNICAL PARAMETERS

Power consumption	From 20W to 1920W
Lumen output	From 3,000 to 221,000 lm
Input voltage options	12 or 24VDC. 240 or 415VAC
LED chip drive current	350mA, 530mA, 700mA, 1050mA, 1400mA
Power factor	≥0.9 at full load
Surge protection	Imax 20kA
LED chips / Efficacy	High performance / To 140+ lm/W
Driver	Inventronics / Philips Xitanium
Driver locations	Built-in / Remote - Wide, Slim-line or Stacked
Lighting controls/Dimming	PE cell, Dimmable 1-10VDC, DALI
Bracket types available	Spigot, wall, ceiling mounts
Emergency option	Available on some fittings to 40W

Colour temperature	2200, 3000, 4000, 5000, 5700°K. Amber, Green, RGB
CRI	RA >70. RA 80 also available as an option
Light distribution	IESNA Types III, IV, V. 16 lensing option in total
Light spill control	Built-in optical spill control
IP Rating / IK Rating	IP67 / IK10
Composition - lenses	Polycarbonate - no glass
Composition - modules	Aluminium, black
Composition - housing	Aluminium with polyester coating (>100 microns)
Housing colour	Black, Grey (RAL7004) White, Bronze, other RAL
Working temperature	-40 to 50 °C
Service life	>50,000 hours
Warranty	5 years

tigerlight

T 1300 184 437 **F** 02 9913 8876

 $\hbox{\bf E} \ \ in fo@tiger light.com.au$

National Support & Distribution Centre Unit 8, 1 Vuko Place, Warriewood, NSW 2102 Western Australia Office & Warehouse Unit 3, 1 Distinction Road, Wangara, WA 6065

