



Introducing  
the all new  
**TIGERCub**



**The original integrated LED  
downlight has been upgraded.**

Now 10W ▪ More compact ▪ Dimmable  
Rated IC-F covered & abutted ▪ 3yr warranty



**TIGERCub** 2.0





# Tiger Cub<sup>2.0</sup> LED Downlight Now 10W - Dimmable

Updating the original all-in-one LED downlight  
IC-F rated - covered and abutted  
90mm cut-out - 1.2 m flex & plug



## Updating the original Tiger Cub downlight

Fully integrated driver - no separate LED driver needed  
Very low heat output with patented heat-sink  
Plasticized aluminium body with PC diffuser  
Excellent light quality & output - 820 lumens (CW)  
30,000+ hour service life.

## Diffused design for modern architectural finish

White, low-profile shape fits flat against ceiling  
Wide 110 degree beam spread for even light distribution  
Diffuser provides soft light with no glare.

## Dimmable

Dims with common universal dimmers.

## IC-F Rated - Covered & Abutted

Suitable for direct mounting on normally flammable surfaces  
Suitable for covering with insulation material.

Applicable Standards:  
AS/NZS 60598.2.2:2001 in conjunction with AS/NZS 60598.1:2003  
AS/NZS 61347.2.13:2013 in conjunction with AS/NZS 61347.1:2002



# TIGERcub<sup>2.0</sup>

## Applications



- Domestic, retail and commercial lighting
- Where energy ratings are important
- Wherever architectural quality lighting is required.



**SNAP-ON ACCESSORY:**  
STAINLESS STEEL FASCIA  
Simply snaps onto standard Cub fitting a for quality metallic look.  
Reduces inventory costs - no need to stock 2 different skus.

## Technical parameters

Power consumption	10W
Size & cut-out	112mm Diam x 57mm H; 90mm cut-out
Colour temperature	3000K (WW) 4000K (CW)
Lumen output	800 lm (WW) 820 lm (CW)
LED type	High efficiency SMD
Input voltage	220-240V AC, 50/60Hz
CRI	>85
Beam angle	110°
IP Rating	IP44 below ceiling / IP40 above
Product lifespan	30,000+ hours
Operating temp	-20° to +40° C
Flex & plug	1.2m flex supplied, with 2 pin plug
Insulation rating	IC-F Covered and Abutted
Fitting body	Diecast aluminium, white PC coating
Diffuser	Polycarbonate
Dimmers supported	Universal dimmers
ORDER CODES:	Warm White Cool White
TIGER CUB 10W	DSCUB10WW DSCUB10CW
BRUSHED STAINLESS FASCIA	DSSF



Quality packaging

